
ALL WEATHER SEALANT

Revision 07/03/2007

Page 1 of 2

TECHNICAL DATA:	<i>Base:</i> Copolymers <i>Consistency:</i> Stable pasta <i>Curing system:</i> Physical drying <i>Skin formation (20°C/65%/ R.H.):</i> Ca. 10 minutes <i>Shrinkage:</i> Ca. 30% <i>Specific gravity (DIN 53479):</i> 1,00 g/mL <i>Temperature resistance:</i> -20°C to +90°C <i>Maximum allowed distortion:</i> 10%
PRODUCT:	All Weather Sealant is a plasto-elastic sealant that adheres onto most surfaces even when damp or under water. Ideal as an emergency repair product or as a general sealant where the job must be done even in the rain. It is a ready to use cartridge and applied with a sealant gun.
CHARACTERISTICS:	Totally transparent Easy to apply and tool 10% movement accommodation good slump resistance solvent based very good adhesion on many materials, even under water
APPLICATIONS:	All usual building substrates including polycarbonate, wood metals, plastics, brick, concrete, MDF, glass Emergency repair of active leaks
PACKAGING:	<i>Colour:</i> white, clear, grey, black <i>Packaging:</i> cartridge 310 ml
SHELF LIFE:	At least 12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C. Do not expose to frost.
SURFACES:	<i>Type:</i> all usual building surfaces. Do not apply on PVC, PE, PP, PTFE and bituminous substrates <i>State of Surface:</i> clean, free of dust and grease <i>Preparation:</i> no preparation needed We recommend a preliminary compatibility test.
JOINT DIMENSIONS:	<i>Minimum Width:</i> 5 mm <i>Maximum Width:</i> 10 mm <i>Minimum Depth:</i> 5 mm <i>Recommendation:</i> depth = width

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.

ALL WEATHER SEALANT

Page 2 of 2

APPLICATION:*Method:* caulking gun*Application temperature:* +1°C to +30°C*Clean:* with white spirit immediately after use*Repair:* with All Weather Sealant**HEALTH- AND SAFETY
RECOMMENDATIONS:**

Apply the usual industrial hygiene.

Consult the label for more information.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.