

ASTROflame[®] DOOR PROTECTION

Glazing Tape



Trade Name: ASTROTAPE



Tested to BS476: Part 22: 1987

Available in Brown, White or Black

½ hour Fire Rating

Easy & Clean Application

A pliable re-shaped strip that bonds well to Wood & Glass

LANTAC Building Control Approval.

NHBC Type Approval.

A flexible self adhesive polymer based extruded intumescent material suitable for sealing wired or fire resistant glazing into wooden fire doors and fire resistant partitions.

On exposure to heat from a fire Astroflame Intumescent tape swells, thus prohibiting smoke and flame from passing through the aperture between wood and glass, providing resistance in excess of 1/2 hour.

Supplied in roll form it offers the user a high performance, non load bearing tape for accurate placement, with no waste and requiring no specialist applications.

Availability

CODE	COLOUR	SIZE
AFIT12B	BROWN	12mm x 3mm x 15mtr
AFIT12W	WHITE	12mm x 3mm x 15mtr
AFIT12BLK	BLACK	12mm x 3mm x 15mtr

Colours

Available in:- Brown, White or Black

Packing

12 rolls per carton

To Order & Specify

Please quote - Quantity/Tradename/Product Ref./Colour/ etc,
Typical wording:- 24/ ASTROTAPE / AFT12B / BROWN

Fire Tests Or Assessment

Warrington Fire Research: Global Assessment
C100767 Trada/Chiltern: RF40523
LANTAC Building Control Approval.
NHBC Type Approval.

Health And Safety

The product does not present any known health hazards during or after installation.
Normal good industrial and personal hygiene practices should be observed.

Areas For Use-Glazing

When glazing internally, using wired or fire resistant glass, the entire glazing system should be able to withstand the effects of the fire for as long as the glass, therefore Astroflame Intumescent tape should be used in this area.

Astroflame (Fire Seals) Ltd.
Intumescent House
Unit 8 The IO Centre
Stephenson Road
Segensworth
FAREHAM
ENGLAND PO15 5RU

Tel: 0800 019 7610 Fax: 0800 019 7611
International - Tel: +44 1329 844 500 Fax: +44 1329 844 600
eMail: sales@astroflame.com